

Mr. Anthony D. Barfield, Art Unit 3636; 09/554,464; Docket No: PAT6C; Giok Djien Go; -22-

What is claimed:

1. A restraint system equipped with a shoulder holder to increase survival chance in a real-world accident of a vehicle, train or an aeroplane or in an inflight turbulence, comprising  
5 a seat belt (1d, 1e), consisting of several belt portions, at least one latch plate, a buckle assembly, a belt pretensioner and belt fittings;  
a shoulder holder (10d), having a pair of shoulder caps (10.2d), which, when in a resting position, are located in a seat backrest (3.2d, 3.2e); and  
a manually-operated rotatable device (28), having a pair of rotatable levers (28.5), retained  
10 by stop pieces (28.9) in the resting position, where the rotatable levers (28.5), having first ends, connected to the pair of shoulder caps (10.2d), and second ends, connected to each other by a shaft (28.7), are rotatably attached to a pair of casings (29), each of which, defined by an L-shaped plate (28.4) and two outer tubes (28.1, 28.2), connected to each other by a coupling wall (28.3), is height-adjustable, latchable and guided by  
15 inner tubes (71, 72) of a seat backrest frame (3.4d, 3.4e);

wherein

a passenger is restrained by the seat belt (1d, 1e) and his shoulders are restrained by the shoulder caps (10.2d), moved by the rotatable device, manually-operated, from the resting position to an operative position;  
20 where at least one shoulder belt portion of the seat belt (1d, 1e) is extended over the respective shoulder cap and a U-shaped plate (10.15) thereof, when the rotatable levers (28.5) are manually rotated, causing release cams (28.6) of the rotatable levers to force a rotation of lock pawls (28.8), pre-loaded by first springs (28.10), thereby permitting locking pins (28.12), pre-loaded by second springs (28.13) and loosely guided in guide  
25 tubes (28.11), to move into holes (28.14) of the casings (29) and block the rotatable levers in both directions.

2. A restraint system equipped with a shoulder holder to increase survival chance in a real-world accident of a vehicle, train or an aeroplane or in an inflight turbulence, comprising  
a seat belt (1, 1e), consisting of several belt portions, at least one latch plate, a buckle  
30 assembly, a belt pretensioner and belt fittings;

G-US 010904 2-space

Mr. Anthony D. Barfield, Art Unit 3636; 09/554,464; Docket No: PAT6C; Giok Djien Go; -23-

a shoulder holder (10e), having a pair of shoulder caps (10.2e), which, when in a resting position, are located on an upper portion of a seat backrest (3.2d, 3.2e); and  
a motor-driven rotatable device (28a), having a drive apparatus (80) and a pair of rotatable levers (28.5a), having first ends, connected to the pair of shoulder caps (10.2e), and  
5 second ends, connected to each other by a shaft (28.7), are rotatably attached to a pair of casings (29a), each of which, defined by an L-shaped, partly laterally closed and partly laterally open plate (28.4a) and two outer tubes (41e, 41f), connected to each other by a coupling wall (28.3), is height adjustable, latchable and guided by inner tubes (71, 72) of a seat backrest frame (3.4d, 3.4e); and  
10 vibration-dampening energy absorbers (40e, 40f), having a number of clamping elements (42e, 42f) provided with sites of predetermined fracture (s), biased, arranged along the outer tubes (41e, 41f) and tautly, less tautly and/or loosely connected to the pair of rotatable levers via stop pieces (28.9a) by corresponding wires (47e, 47f);

wherein

15 a passenger is restrained by the seat belt (1, 1e) and his shoulders are restrained by the shoulder caps (10.2e), moved by the rotatable device, driven by the drive apparatus (80), from the resting position to an operative position;

where at least one shoulder belt portion of the seat belt (1, 1e) is extended over the respective shoulder cap and a U-shaped plate (10.15) thereof, when the rotatable levers (28.5a) are rotated by the drive apparatus (80), causing release cams (28.6a) of the  
20 rotatable levers to force a rotation of lock pawls (28.8a), pre-loaded by first springs (28.10a), thereby permitting locking pins (28.12), pre-loaded by second springs (28.13) and loosely guided in guide tubes (28.11), to move into holes (28.14) of the casings (29a) and block the rotatable levers in one direction;

25 where in the real-world accident or in the inflight turbulence a forward motion of the torso and head rotates the rotatable levers in another direction through the openings of the L-shaped, partly laterally closed and partly laterally plates (28.4a), thus moving the clamping elements (42e, 42f) along the corresponding tubes (41e, 41f) resulting in a work of deformation and friction, during which vibrations are dampened and a stored  
30 energy is released by fracture of the sites of predetermined fracture of the clamping elements in excess of respective threshold values.

G-US 010904 2-space

Mr. Anthony D. Barfield, Art Unit 3636; 09/554,464; Docket No: PAT6C; Giok Djien Go; -24-

3. A restraint system equipped with a shoulder holder to increase survival chance in a real-world accident of a vehicle, train or an aeroplane or in an inflight turbulence, comprising a seat belt (1, 1b, 1e), consisting of several belt portions, at least one latch plate, a buckle assembly, a belt pretensioner and belt fittings;

5 a shoulder holder (10, 10b, 10f), having a pair of shoulder caps (10.2, 10.2b, 10.2f) with open apertures to receive the belt portions;

a pair of latch plates (10.1b), connected to the shoulder caps (10.2, 10.2b, 10.2f), with open apertures, in which the belt portions are loosely secured by quick-release pins (10.10), when the shoulder holder and the seat belt are fitted together, and released by

10 withdrawal thereof for removal, when the shoulder holder is withdrawn; and

at least one pair of buckle assemblies (18a / 19a to 18n / 19n), attached in a seat backrest (3.2a, 3.2c);

wherein

15 a passenger is restrained by the seat belt (1, 1b, 1e) and his shoulders are restrained by the shoulder caps (10.2, 10.2b, 10.2f) upon plug-in connection of the latch plates (10.1b) with the buckle assemblies (18a / 19a to 18n / 19n); and

at least one shoulder belt portion of the seat belt (1, 1b, 1e) is extended over the open aperture of the corresponding shoulder cap and loosely secured in the open aperture of the latch plate.

20 4. A restraint system equipped with a shoulder- and neck holder to increase survival chance in a real-world accident of a vehicle, train or an aeroplane or in an inflight turbulence, comprising

a seat belt (1a, 1c, 1e), consisting of several belt portions, at least one latch plate, a buckle assembly, a belt pretensioner and belt fittings;

25 a one-piece shoulder- and neck holder (10a, 10c), defined by a neck cap (10.4a, 10.4c) and a shoulder cap (10.2a, 10.2c) with open apertures to receive the belt portions;

a pair of latch plates (10.1b), connected to the shoulder cap (10.2a, 10.2c), with open apertures, in which the belt portions are loosely secured by quick-release pins (10.10), when the one-piece shoulder- and neck holder and the seat belt are fitted together, and

30 released by withdrawal thereof for removal, when the one-piece shoulder- and neck holder is withdrawn; and

G-US 010904 2-space

Mr. Anthony D. Barfield, Art Unit 3636; 09/554,464; Docket No: PAT6C; Giok Djien Go; -25-

at least one pair of buckle assemblies (18a / 19a to 18n / 19n), attached in a seat backrest (3.2a, 3.2c);

wherein

a passenger is restrained by the seat belt (1a, 1c, 1e) and his shoulders and his neck are

5 restrained by the shoulder cap (10.2a, 10.2c) and neck cap (10.4a, 10.4c) upon plug-in connection of the latch plates (10.1b) with the buckle assemblies (18a / 19a to 18n / 19n); and

at least one belt shoulder portion of the seat belt (1a, 1c, 1e) is extended over the corresponding open aperture of the shoulder cap and loosely secured in the open  
10 aperture of the respective latch plate.

5. The restraint system according to claim 2, wherein the shoulder cap (10.2e), recessed about a supporting tube (3.61) of a head rest (3.6), is reinforced by a reinforcing plate (10.13).

6. The restraint system equipped with a shoulder- and neck holder according to claim 2,  
15 further comprising a neck holder, having a pair of neck caps (10.4, 10.4b), attached to the pair of shoulder caps (10.2e), to restrain the passenger's neck in the operative position.

7. The restraint system according to claim 6 wherein the drive apparatus (80) is activated by a separately operated switch.

8. The restraint system according to claim 6, wherein the drive apparatus is activated by a  
20 controller, monitoring the speed, in excess of a threshold speed.

9. The restraint system according to claim 6, wherein the drive apparatus is activated by an accelerator pedal.

10. The restraint system according to claim 6, wherein the drive apparatus is activated when a sensor senses an acceleration, which exceeds a threshold acceleration.

25 11. The restraint system according to claim 6, wherein upon a pressure on a release button (87a to 87c) of the seat the drive apparatus (80) moves the shoulder- and neck holder back from the operative position to the resting position.

G-US 010904 2-space

Mr. Anthony D. Barfield, Art Unit 3636; 09/554,464; Docket No: PAT6C; Giok Djien Go; -26-

12. The restraint system according to claim 6, wherein the buckle assembly of the seat belt has a master release button (84), provided with a release wire connecting to a switch of the drive apparatus (80), where the master release button (84), when depressed, disengages the latch plate and moves the shoulder- and neck holder back from the operative position to the resting position.

13. The restraint system equipped with a shoulder- and neck holder according to claim 3, further comprising a neck holder, having a pair of neck caps (10.4, 10.4b), insertably attached to the pair of shoulder caps (10.2, 10.2b, 10.2f), to restrain the neck upon use, where the neck caps can be detached therefrom and removed.

14. The restraint system according to claim 13, wherein the shoulder- and neck holder (10, 10b, 10f) is provided with at least one energy absorber (10.3, 10.3a, 10.5, 10.5a, 10.5c).

15. The restraint system according to claim 14, wherein the energy absorber is fastened to the cap by an adhesive fastener and detachable therefrom by opening the fastener.

16. The restraint system according to claim 3, wherein the shoulder cap is shoulder-shaped.

17. The restraint system according to claim 14, wherein the energy absorber is shoulder-shaped.

18. The restraint system according to claim 13, wherein the neck cap is neck-shaped.

19. The restraint system according to claim 14, wherein the energy absorber is neck-shaped.

20. The restraint system according to claim 19, wherein the energy absorber (10.5a), arranged in the neck cap (10.4a), serves as a neck collar having a wide portion for the chin.

21. The restraint system according to claim 3, wherein the latch plate of the holder is provided with an energy absorber (10.9).

G-US 010904 2-space

Mr. Anthony D. Barfield. Art Unit 3636; 09/554,464; Docket No: PAT6C; Giok Djien Go; -27-

22. The restraint system according to claim 13, wherein the shoulder- and neck cap, provided with a flange (10.12), is adjustable in height by rotating a bolt (10.7) in a threaded hole of the flange (10.12).

23. The restraint system according to claim 13, wherein the shoulder- and neck cap, provided with a flange (10.12f), is adjustable in width by rotating a bolt (10.6a) in a threaded hole of the flange (10.12f).

24. The restraint system equipped with the shoulder- and neck holder and with vibration-dampening energy absorbers according to claim 13, further comprising at least one vibration-dampening energy absorber (30, 40, 50), which consists of  
10 a retaining element (31, 41, 51), serving as a member of a seat frame, generally representing a seat-cushion- or seat backrest frame, and  
at least one clamping element (32, 32.1 to 32.n, 42, 42.1 to 42.n, 52, 52.1 to 52.n),  
connected to the buckle assembly of the seat by means of at least one control-wire (37, 47, 57), biased, arranged along the retaining element and provided with sites of  
15 predetermined fracture (s), which have at least one threshold value.

25. The restraint system according to claim 24, wherein the retaining element is integrated into the seat frame.

26. The restraint system according to claim 24, wherein the clamping element has open and tube-shaped profile.

20 27. The restraint system according to claim 24, wherein the retaining element is tube-shaped.

28. The restraint system according to claim 24, wherein a longitudinal rib (41.1, 51.1) is arranged to the retaining element.

29. The restraint system according to claim 28, wherein both edges of the clamping  
25 element are loosely guided by the longitudinal rib in longitudinal direction.

30. The restraint system according to claim 28, wherein a stop element (41.3) is arranged to the longitudinal rib.

G-US 010904 2-space

Mr. Anthony D. Barfield, Art Unit 3636; 09/554,464; Docket No: PAT6C; Giok Djien Go; -28-

31. The restraint system according to claim 28, wherein the thickness of the longitudinal rib increases in longitudinal direction, in which the clamping element moves.

32. The restraint system according to claim 24, wherein the clamping element is cone-shaped.

5 33. The restraint system according to claim 24, wherein the retaining element (51) is cone-shaped.

34. The restraint system according to claim 24, wherein at least one stop pin (46, 46.1 to 46.n) is laterally arranged to the retaining element, where the stop pin blocks a movement of the clamping element, thus resulting in fracture of the sites of predetermined fracture.

10 35. The restraint system according to claim 24, wherein contact surfaces of the retaining element have arbitrary friction coefficients ( $\mu_0$ ).

36. The restraint system according to claim 24, wherein contact surfaces of the retaining element are provided with a soundproofing material (83).

15 37. The restraint system according to claim 24, wherein contact surfaces of the clamping element have arbitrary friction coefficients ( $\mu_0$ ).

38. The restraint system according to claim 24, wherein contact surfaces of the clamping element are provided with a soundproofing material (83).

20 39. The restraint system according to claim 29, wherein end portions of a complementary wires (37a1), connected to the control-wire (37), are inserted into both cylinder-shaped edges (37c1) of the clamping elements (32) and secured by clamping the cylinder-shaped edges (37c1).

40. The restraint system according to claim 24, wherein the clamping element is provided with a pair of ribs, whereto several pairs of adjusting holes ( $L_1$  to  $L_n$ ) are arranged.

G-US 010904 2-space

Mr. Anthony D. Barfield, Art Unit 3636; 09/554,464; Docket No: PAT6C; Giok Djien Go; -29-

41. The restraint system according to claim 24, wherein a set of vibration-dampening energy absorbers comprises the retaining element, at least one stop pin, at least one stop element, one control-clamping element, connected to the control-wire, and complementary clamping elements with/without sites of predetermined fracture, where all clamping elements, arranged along the retaining element, are tautly, less tautly and/or loosely connected to each other by means of complementary wires.

42. An energy-absorbing, vibration-dampening device according to claim 41, comprising a couple member (1.2a, 1.2b) and the sets of vibration-dampening energy absorbers, the control-wires of which are tautly, less tautly and/or loosely connected to the couple member.

43. The restraint system according to claim 42, wherein a guide piece (4.7a), fastened to the seat frame, has  
a pair of engaging parts (4.10a), form-locking connected to the corresponding apertures of a housing (4.8a) of the buckle assembly; and  
a recess (4.5a) to loosely guide a tie band (1.1a), having a first and second end connected to the buckle assembly and the couple member.

44. The restraint system according to claim 42, wherein a guide piece (4.7b), fastened to the seat frame, has  
a pair of engaging parts (4.10b), form-locking connected to the corresponding apertures of a housing (4.8b) of the buckle assembly; and  
a longitudinal groove (4.5b) to loosely guide a tie band (1.1b), having a first and second end connected to the buckle assembly and the couple member.

45. The restraint system according to claim 42, wherein a housing (4.8c), movable along a pair of tubes (27.3) of the seat backrest frame and latchable thereon, has  
an aperture to receive an engaging part (4.10c) of the buckle assembly, through a hole (2.3) of which a wire is protruded and both end portions of the wire, serving as tie bands, are secured by a mutual bracket (1.7); and  
two holes (4.5c) to loosely guide the tie bands, connected to the couple members.

G-US 010904 2-space



Mr. Anthony D. Barfield, Art Unit 3636; 09/554,464; Docket No: PAT6C; Giok Djien Go; -30-

46. The restraint system according to claim 13, wherein the buckle assembly of the seat belt has a master release button (84),

provided with release wires connecting to electrical motors (4.2b) of release buttons of the pairs of buckle assemblies, to one of which the latch plates of the holder are plug-in  
5 connected;

where the master release button (84), when depressed, disengages all the latch plates of the holder and seat belt.

47. The restraint system according to claim 13, wherein the buckle assembly of the seat belt has a master release button (84),

10 provided with release cables (4.2) connecting to release buttons of the pairs of buckle assemblies, to one of which the latch plates of the holder are plug-in connected;  
where the master release button (84), when depressed, disengages all the latch plates of the holder and seat belt.

48. The restraint system according to claim 3, wherein the shoulder holder is attached to  
15 the seat for the purpose of storage and detachable therefrom by depressing a release button (87a to 87c) of the seat.

49. The restraint system according to claim 13, wherein the shoulder- and neck holder is attached to the seat for the purpose of storage and detachable therefrom by depressing a release button of the seat.

20 50. An energy-absorbing, vibration-dampening safety seat according to claim 49, wherein sets of vibration-dampening energy absorbers, the seat belt, holder and seat are integrated into a safety adult-seat;

which is transformed into a safety child-seat when a detachable front portion of the seat cushion (3.1a) serves as a shoulder- and neck holder (10a), the latch plates of which are  
25 plug-in connected to one of the pairs of buckle assemblies (18a / 19a to 18n / 19n) of the seat backrest, to restrain shoulders and a neck of a belted child and the space thereof is exploited to accommodate legs of the child sitting on the rear portion thereof,  
where the safety child-seat can be converted back into the safety adult-seat.

G-US 010904 2-space

Mr. Anthony D. Barfield, Art Unit 3636; 09/554,464; Docket No: PAT6C; Giok Djien Go; -31-

**51.** An energy-absorbing, vibration-dampening safety baby-cot according to claim 50,  
wherein

the safety child-seat is transformed into a safety baby-cot when the seat backrest is flipped  
downwards;

5 where the safety baby-cot can directly be converted back either into the safety child-seat or  
into the safety adult-seat.

**52.** The restraint system according to claim 13, wherein

a common release button (840), located on the seat cushion, is provided with release  
cables (4.2) connecting to release buttons of the pairs of buckle assemblies, to one of  
10 which the latch plates of the holder are plug-in connected;

where the common release button (840), when depressed, disengages the latch plates of  
the holder while the passenger remains belted.

G-US 010904 2-space